





# F Series

## Mini Filters and Dryers



-  **FILTER SEPARATOR (FS)**
-  **COALESCER FILTER (FC)**
-  **DESICCANT DRYER( FD)**



**EFS**



**EFC**



**EFD**

### Description

F Series Filter effectively reduce contamination in your air stream, protecting critical processes and valuable equipment, while maintaining a low pressure drop throughout the life of the filter element to ensure and efficiently preparing the air for point-of-use applications.



### Specifications and ordering information:

Housing	Air flow 100 psig scfm	Inlet/ Outlet NPT in	Dimensions (in)			Replacement kit	Weight (lbs)
			A	B	C		
FS- 1/2	20	1/2	3 1/8	7 1/2	6 1/2	EFS-1/2	1.2
FS-1	40	1	3 5/8	11 3/8	10	EFS-1	3.8
FC- 1/2	20	1/2	3 1/8	7 1/2	6 1/2	EFC-1/2	1.2
FC-1	40	1	3 5/8	11 3/8	10	EFC-1	3.8
FD- 1/2	20	1/2	3 1/8	7 1/2	6 1/2	EFD-1/2	1.2
FD-1	40	1	3 5/8	11 3/8	10	EFD-1	3.8

Housing 1/2": Maximum inlet temperature: 100°F (38°F) Maximum inlet pressure: 130 psig-Plastic Bowl  
 Housing 1": Maximum inlet temperature: 100°F (38°F) Maximum inlet pressure: 150 psig-Metal Bowl  
 Drainage: FS ( float drain) FC/FD (manual drain)